

# ASLAN TL 10

## Transfer liquid for effective wet applications

Transfer liquid for an effective wet application of ASLAN self-adhesive films. The ASLAN TL 10 is mixed with water and will be delivered in 0,5 litre bottles including an empty spraying bottle.

For additional information please contact our technical advisory service:  
**+49 (0) 22 04. 7 08-80**

---

## Chemical characteristics

Not flammable, liquid dilution from anionic and non-ionic surfactants and alcohols.  
No requirement to label  
An EEC safety document is available.

---

## First aid measures

In case of eye contact thoroughly rinse with cold water.

---

## Processing

Before the application the surface should be cleaned thoroughly and evenly be sprayed with the diluted ASLAN TL 10. Afterwards align the self-adhesive film with the application tape on the still wet surface, laminate thoroughly on the surface and remove the spare liquid by using a squeegee.  
Carefully remove application tape in angle of 180° and remove any remaining fluid with a soft and absorbent cloth.  
During wet application the adhesive might be coloured white. This will - subject to weather conditions - disappear within a few days.

---

### State: 10|2013

All technical data and advice is based on our experience and measured testing that we believe to be reliable. It remains the customer's responsibility to test the suitability of our products for the intended purpose.

The quality of our products is regularly examined, upgraded and developed. We take the right, without prior notice, to adjust, upgrade and improve the chemical structures or physical characteristics of our products in accordance with our latest knowledge.

---

**ASLAN, Schwarz GmbH & Co. KG**

Oberauel 2 · 51491 Overath · Germany

**phone** +49 (0) 2204.708 80 · **fax** +49 (0) 2204.708 50

**e-mail** info@ASLAN-Schwarz.com



[www.ASLAN-Schwarz.com](http://www.ASLAN-Schwarz.com)

**ASLAN**®  
EXPERTISE IN SELF-ADHESIVE FILMS