

ASLAN E

Self-adhesive pelmet film

This single-sided self-adhesive rigid PVC-film is ideal to produce pelmets for window decorations. The film is characterised by a very high opacity and has a high form stability. A bando-print with the most popular pelmet forms on the release liner helps in cutting the film into the required shape.

For additional information please contact our technical advisory service:
+49 (0) 22 04. 7 08-80

Construction

| | | |
|------------------|------------------------------|--|
| face-film: | rigid PVC | |
| thickness: | ~ 300 µm | |
| weight: | ~ 380 µm | |
| adhesive: | acrylic pressure adhesive | square quantity: ~ 35 g/m ² |
| release liner: | silicone paper , bando-print | square weight: ~ 63 g/m ² |
| total weight: | ~ 350 µm | |
| total thickness: | ~ 480 µm | |

Characteristics

| | | |
|-----------------------------------|--|----------------------------------|
| adhesive strength: (ASTMD-903) | immediately after 1 week | ~ 10 N/25 mm ~ 20 N/25 mm |
| temperature: | application temperature: service temperature range: | min. 15°C -30 °C up to +80 °C |

ASLAN, Schwarz GmbH & Co. KG
Oberauel 2 · 51491 Overath · Germany
phone +49 (0) 2204.708 80 · **fax** +49 (0) 2204.708 50
e-mail info@ASLAN-Schwarz.com



www.ASLAN-Schwarz.com

ASLAN®
EXPERTISE IN SELF-ADHESIVE FILMS

ASLAN E

Processing

| | |
|----------------------|--|
| application: | Dry application only. |
| storage life: | Before application the films can be stored for minimum 3 years from date of production. The film must be stored at room temperature (15-25 °C) and a relative humidity of the air of 50-60%. To avoid pressure points appearing on the roll surface, we recommend the rolls be stored either vertical standing or for this purpose designed 'hanging' racks. |

State: 10|2013

All technical data and advice is based on our experience and measured testing that we believe to be reliable. It remains the customer's responsibility to test the suitability of our products for the intended purpose.

The quality of our products is regularly examined, upgraded and developed. We take the right, without prior notice, to adjust, upgrade and improve the chemical structures or physical characteristics of our products in accordance with our latest knowledge.

ASLAN, Schwarz GmbH & Co. KG
Oberauel 2 · 51491 Overath · Germany
phone +49 (0) 2204.708 80 · **fax** +49 (0) 2204.708 50
e-mail info@ASLAN-Schwarz.com



www.ASLAN-Schwarz.com

ASLAN® 
EXPERTISE IN SELF-ADHESIVE FILMS