

ReApply Whiteboard ASLAN RA 695

Adhesive, reusable whiteboard film

The products from the ASLAN ReApply series are ASLAN functional films that are equipped with a revolutionary adhesive system and can be easily applied to smooth surfaces. The top of the ReApply is a combination of different variations of the well-known ASLAN memo board films.

After use the ASLAN ReApply can be rolled up, stored away and used again when required.

The face film of the ReApply Whiteboard ASLAN RA 695 has an easy-to-clean surface. For example, glass and kitchen surfaces, doors, tiles, etc. can be transformed into whiteboards in no time at all. Additionally, using whiteboard markers, it is guaranteed to clean easily without the ghosting effect of former writing. When it is no longer needed simply remove it, roll it up and store it away for later use. If ReApply does not adhere well to the surface, such as matt and slightly textured surfaces, this can be increased by lightly spraying the back of the film with water.

For further information or questions regarding special applications please contact our technical advisory service: **+49 2204.708-80**

Construction

Face film:	PVC-free adhesive system in combination with PET-PVC-composite, polymeric softened, white, glossy
Thickness:	~ 360 µm
Release liner:	no liner

Characteristics

Temperature:	application temperature:	min 15 °C (59 °F)
	service temperature range:	0 °C (32 °F) up to +80 °C (176 °F)

ReApply Whiteboard ASLAN RA 695

Processing

Application:

The film can be applied dry to smooth surfaces. For matt and slightly rough surfaces, it is recommended to dampen (mist-damp) the substrate to be applied with clear water by spraying or applying with a cloth. Please check the substrates for moisture resistance beforehand. Slight deformations of the material, such as protruding corners, can either be pressed onto the substrate with moisture.

After use, the dry film can be rolled up, stored and reused. To do this, use a core that is at least 3" in diameter. The visible side of the material should always be rolled outwards (foam inside).

Important!

We do not recommend a large-scaled application of whiteboard films with mounting tapes. The writable surface of the film can be damaged by taking off the tape so removability cannot be guaranteed anymore.

Cleaning:

Writings with whiteboard markers can be easily wiped off dryly using a microfibre cloth, without leaving any ghosting and shadows. If you used by mistake inappropriate pens e.g. a permanent marker you can clean the films with alcohol or white gas for cleaning purposes without leaving any residues.

Storage:

Before application the films can be stored up to 2 years from date of production. The film must be stored at room temperature (15-25 °C / 59-77 °F) and a relative humidity of the air of 50-60%. To avoid pressure points appearing on the roll surface, we recommend the rolls be stored either vertical standing or for this purpose designed 'hanging' racks.

The material should only be transported or stored rolled on core (3") with the visible side facing outwards.

Stand 10|2021

All technical data and advice is based on our experience and measured testing that we believe to be reliable. It remains the customer's responsibility to test the suitability of our products for the intended purpose. The quality of our products is regularly examined, upgraded and developed. We take the right, without prior notice, to adjust, upgrade and improve the chemical structures or physical characteristics of our products in accordance with our latest knowledge.