

# TextileMask ASLAN S 390

## Self-adhesive stencil film for painting and lacquering works on uncoated textiles

This self-adhesive film is due to its special adhesive excellent for painting and lacquering works of uncoated textiles. Fabrics, awnings, canvas and advertising banners can be easily decorated with paint and lacquering. The residue-free removable film adapts perfectly to the surface and allows sharply contoured letterings or paintings.

For any further information please contact our technical advisory service: **+49 2204 70880**

### Construction

Face film:	Double PVC-film	
Thickness:	~ 180 µm	
Adhesive:	Acrylic pressure adhesive	Square quantity: ~ 40 g/m <sup>2</sup>
Release liner:	Silicone cardboard	Square weight: ~ 140 g/m <sup>2</sup>

### Characteristics

Adhesive strength (ASTMD-903):	immediately: after 72 hours:	~ 9 N/25 mm ~ 13 N/25 mm
Dimensional stability:	2 hours with 70° C on acrylic glass	no longitudinal or lateral contraction
Tensile strength:	DIN 53 455	longitudinal ~ 150 % lateral ~ 170 %
Combustibility:	Stuck on aluminium, the film is self-extinguishing.	
Temperature:	Application temperature: Service temperature range:	min. 15 °C -30 °C up to +80 °C

**ASLAN, Schwarz GmbH & Co. KG**  
Oberauel 2 · 51491 Overath · Germany  
fon +49 2204 70880 · fax +49 2204 70850  
e-mail info@ASLAN-Schwarz.com



[www.ASLAN-Schwarz.com](http://www.ASLAN-Schwarz.com)

**ASLAN**®

EXPERTISE IN SELF-ADHESIVE FILMS

# TextileMask ASLAN S 390

---

## Processing

---

### Application:

Dry application only. Humidity, longer application processes and high temperatures increase the adhesive strength.

For the application of letterings etc. we recommend our application tape LowTackTape ASLAN TP 110 respectively the ASLAN TMO.

### Storage:

Before application the film can be stored for minimum 2 years from date of production. The film must be stored at room temperature (15-25 °C) and a relative humidity of the air of 50-60%. To avoid pressure points appearing on the roll surface, we recommend the rolls be stored either vertical standing or for this purpose designed 'hanging' racks.

---

## State 9|2019

All technical data and advice is based on our experience and measured testing that we believe to be reliable. It remains the customer's responsibility to test the suitability of our products for the intended purpose.

The quality of our products is regularly examined, upgraded and developed. We take the right, without prior notice, to adjust, upgrade and improve the chemical structures or physical characteristics of our products in accordance with our latest knowledge.

---

**ASLAN, Schwarz GmbH & Co. KG**  
Oberauel 2 · 51491 Overath · Germany  
fon +49 2204 70880 · fax +49 2204 70850  
e-mail info@ASLAN-Schwarz.com



[www.ASLAN-Schwarz.com](http://www.ASLAN-Schwarz.com)

**ASLAN**<sup>®</sup>  
EXPERTISE IN SELF-ADHESIVE FILMS